



Balkumari, Lalitpur
Email: info@dhunganamultipurpose.com
9860888671, 9851120350

■ Basic parameters EPM 11 Seat

Vehicle dimensions (mm)	4865×1715×2065
Wheelbase (mm)	3050
Wheel base (front/rear) (mm)	1460/1450
Tire specifications	185R14LT
Minimum ground clearance (full load) (mm)	180
Minimum turning radius (m)	6
Maximum speed (km/h)	90
Curb weight kg	1750
GVW(kg)	3050
Endurance mileage/km(NEDC)	280
Maximum gradability %	≥25

■ Motor parameters

Type of motor	Permanent Magnet Synchronous Motor
Peak power/torque (kW/ N.m)	70/230

■ Battery parameters

Type of battery	Lithium Iron Phosphate (LFP)
Battery capacity (kWh)	41.932
Battery fast charge (min)SOC30% to 80%(120KW)	≤30min
Charging ports	GB

■ Braking, suspension, drive mode

Braking system (front/rear)	Front disc/back drum/ABS+EBD
Suspension system (front/rear)	McPherson independent suspension Leaf spring type non-independent suspension
Drive type	Rear-rear-drive

■ Safety

Front disc and rear drum brakes	•
Fog lights	Front -•, back -•
reversing camera	•
Day running lights	•

■ Body accessories

Uphill Assist	•
Central lock + remote key	•
Air conditioning refrigeration system Front)	•
Air conditioning refrigeration system Rear)	•
Air conditioning heating system	•

Warranty

Warranty	5 years or 300000 KM whichever comes earlier
----------	--