





Email: info@dhunganamultipurpose.com 9860888671, 9851120350

Minimum ground clearance (full load) (mm) Minimum turning radius (m) Maximum speed (km/h) Curb weight kg GVW(ka)

Vehicle dimensions (mm)

Wheel base (front/rear) (mm)

Wheelbase (mm)

Tire specifications

Endurance mileage/km(NEDC) Maximum gradability % ■ Motor parameters

■ Basic parameters EPM 18 Seat

5265×1870×2060

3450

1460/1450

195/70R15LT

180

6.35

90

1880

3380

280

≥25

Permanent Magnet

Synchronous Motor

70/230

Lithium Iron Phosphate

(LFP) 53.58

≤30min

GB

Front disc/back

drum/ABS+EBD

McPherson independent suspension

Leaf spring type nonindependent suspension

Rear-rear-drive

Front - , back - •

Type of motor Peak power/torque (kW/ N.m)

■ Battery parameters Type of battery

Battery capacity (kWh) Battery fast charge (min)SOC30% to 80%(120KW)

Charging ports ■ Braking, suspension, drive mode

Suspension system (front/rear)

Braking system (front/rear)

Drive type Front disc and rear drum brakes

Fog lights reversing camera Day running lights

■ Body accessories **Uphill Assist** Central lock + remote key

Air conditioning refrigeration system Front) Air conditioning refrigeration system Rear)

Air conditioning heating system

Warranty Warranty

■ Safety

5 years or 300000 KM whichever comes earlier